

# D160

## Recessed spotlights 35W

- Durable aluminum die-casting housing
- Passive cooling design
- rated voltage 220--240V 50...60Hz
- Zhaga standard for fitting different branded LED COB module
- beam angle available in spot, medium and flood
- powder coated finish in silver, white and black
- Horizontal 355°, Tilting 70°



**Rated Voltage**  
220--240V

**Beam angle**  
  
15° spot  
  
24° medium  
  
36° flood  
  
60° w. flood

**Frequency**  
50...60Hz

**Color**  
  
RAL 9006  
  
RAL 9016  
  
RAL 9005

Ø 145mm  
  
0.95kg  
  
355°  
  
70°

Ø 160  
135

### Ordering information

| Item no. | Description                   | Color            | Beam angle |
|----------|-------------------------------|------------------|------------|
| 2005.01  | recessed spotlight housing    | structure silver | -          |
| 2005.02  | recessed spotlight housing    | structure white  | -          |
| 2005.03  | recessed spotlight housing    | structure black  | -          |
| RE855001 | aluminum reflector spot       | -                | 15°        |
| RE855002 | aluminum reflector medium     | -                | 24°        |
| RE855003 | aluminum reflector flood      | -                | 36°        |
| RE855004 | aluminum reflector wide flood | -                | 60°        |